

## Triplex 2.9 RV Pump



### FEATURES & BENEFITS

- Smooth flow and quiet operation for up to three fixtures
- Equipped with pressure switch to provide "on-demand" service
- Quick connect ports allow for easy installation, winterizing and servicing
- Integrated pulsation dampener to reduce cycling and noise
- Runs dry without damage
- Self-priming
- Built-in thermal protection protects motor from overheating
- Includes bypass valve which allows for consistent performance without use of an accumulator tank

### SPECIFICATIONS

Diaphragm Material:	EP/PP blend
Valve Material:	EPDM
Flowrate:	2.9 GPM (11 LPM)
Max Pressure:	50 psi (3.5 bar)
Size:	4.75" high x 9" long x 6" wide (121mm x 229mm x 152mm)
Weight:	3.5lb (1.6kg)
Strainer :	Not included
Port Fittings:	1/2" (13mm) hose barb, elbow (qty 2); 1/2" (13mm) - 14 NPSM, straight (qty 2)
Pumphead Kit:	50 psi models: 20406045A

MODEL	VOLTS	OPEN FLOW GPM (LPM)	PRESSURE ON/OFF	MAX AMPS	CERTIFICATIONS
R3426144	12V DC	2.9 GPM (11 LPM)	25 psi (1.7 bar)	5.2A	CE, CSA, E8
03526144	12V DC	2.9 GPM (11 LPM)	50 psi (3.5 bar)	7.5A	CSA
R3526144	12V DC	2.9 GPM (11 LPM)	50 psi (3.5 bar)	7.5A	CE, CSA, E8
R3626344	24V DC	2.9 GPM (11 LPM)	40 psi (2.8 bar)	2.6A	CE, E8