

156-00468

HellermannTyton



Article Number: 156-00468

Description: Cable Tie and Edge Clip, 8.0 Long, EC5B, 1–3 mm Panel, 50lb, PA66UV, Black, 100/bag

Base Data	
Local Order Number	156-00468
Type	T50REC5B
Color	Black (BK)
Features and benefits	<ul style="list-style-type: none"> • Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole. • Edge Clip provides low insertion force and high extraction force ideal for assembly environments. • Two piece assembly allows the mount to slide along the strap ensuring proper orientation.
Quantity Per	bag
Product Description	This cable tie and edge clip assembly is ideal for use where holes are not acceptable or where adhesives will fail due to temperature problems. Edge clips are widely used for fixing and bundling cables and wires within automotive, trucking, heavy equipment, solar panel, wind power, and white goods equipment manufacturing.
Global Part Name	T50REC5B-PA66UV/PA66HIRHSUV-BK
Short Description	Cable Tie and Edge Clip, 8.0 Long, EC5B, 1–3 mm Panel, 50lb, PA66UV, Black, 100/bag
Product Dimensions	
Minimum Tensile Strength (Imperial)	50.0lbs
Minimum Tensile Strength (Metric)	225N
Length L (Imperial)	8.0"
Length L (Metric)	200.0mm
Length L2 (Imperial)	0.6"
Fixation Method	EdgeClip, sideways, assembled, 2 piece
Identification Plate Position	none
Length L2 (Metric)	14.0mm
Releasable Closure	No
Variant	Inside Serrated
Width W (Imperial)	0.55"

156-00468

HellermannTyton

Product Dimensions	Width W (Metric)	14.0mm
	Width W2 (Imperial)	0.39"
	Width W2 (Metric)	10.0mm
	Height H (Imperial)	0.61"
	Height H (Metric)	15.5mm
	Height H2 (Imperial)	0.40"
	Height H2 (Metric)	10.16mm
	Bundle Diameter Min. (Imperial)	0.16"
	Bundle Diameter Min. (Metric)	4.0mm
	Bundle Diameter Max. (Imperial)	2.0"
	Bundle Diameter Max. (Metric)	50.8mm
	Panel Thickness Max. (Imperial)	0.12"
	Panel Thickness Max. (Metric)	3.0mm
	Panel Thickness Min. (Imperial)	0.04"
	Panel Thickness Min. (Metric)	1.0mm
	Thickness T (Imperial)	0.05"
	Thickness T (Metric)	1.2mm
Material and Specifications		
	Material	Polyamide 6.6 UV-stabilized (PA66UV) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
	Material Shortcut	PA66HIRHSUV PA66UV PA66UV PA66UV PA66UV PA66UV PA66UV
	Material Cable Tie	Polyamide 6.6 UV-stabilized (PA66UV)
	Flammability	UL 94 V2 UL 94 HB UL 94 HB UL 94 HB UL 94 HB UL 94 HB UL 94 HB
	Operating Temperature	-40°F to +230°F (-40°C to +110°C) -40°F to +185°F (-40°C to +85°C) -40°F to +185°F (-40°C to +85°C) -40°F to +185°F (-40°C to +85°C) -40°F to +185°F (-40°C to +85°C) -40°F to +185°F (-40°C to +85°C) -40°F to +185°F (-40°C to +85°C)

156-00468



Material and Specifications	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	100
	Package Quantity (Metric)	100
	Customs Number(Schedule B)	3926909987
	Weight (Metric)	0.00281227kg
	Weight (imperial)	0.0062lbs