



## SolarRiver-US

**3000 / 3800 / 5000 / 6000 / 7000 / 7600 / 9000 / 10000TLA-US**

### **SIMPLE. FLEXIBLE.**

- Outstanding two MPPT unbalance function, Suited complicated houseroof, Meeting multi-orientations residence.
- More input current, Permitting more strings in parallel.
- Free site selection due to NEMA 3R.

### **OPEN. INTERACTIVE.**

- Interface selection - Ethernet, WIFI for more flexible configuration and system monitoring.
- Multi-lingual 2-line LCD display
- Easy key pad operation

### **SECURE. EFFICIENT.**

- Highest earnings through peak efficiency of 98.0%
- Safe operation due to integrated DC-Switch
- Free access to Samilpower monitoring portal
- 5 years standard guarantee



● Standard features ○ Optional features - Not available

	SolarRiver 3000TLA-US	SolarRiver 3800TLA-US	SolarRiver 5000TLA-US	SolarRiver 6000TLA-US
<b>Input (DC)</b>				
Max. DC power	3300 W	4200 W	5500 W	6600 W
Maximum Usable Power for Each Channel	3300 W	2900 W	3800 W	3800 W
Max. input voltage	550 V			
Full load MPP voltage range / rated input voltage	200 V - 500 V / 400V			
Min. input voltage / initial input voltage	100 V / 150 V			
Max. input current for both MPPT in Parallel	16.5 A	21 A	27.5 A	33 A
Max. usable current per channel (not including Full load MPP voltage range)	16.5 A	14.5 A	19 A	19 A
Max. Input Short Circuit Current per channel	17.4 A	15.5 A	20 A	20 A
Max. Utility Backfeed Current to PV array	0 A			
Number of independent MPP inputs	1	2	2	2
Number of strings	2	4	4	4
<b>Output (AC)</b>				
Rated power (@ 240 V / 60 Hz)	3000 W	3800 W	5000 W	6000 W
Max. apparent AC power	3300 VA	4180 VA	5500 VA	6600 VA
Nominal AC voltage / range	240 V / 211 - 264 V			
AC power frequency / range	60 Hz / 59.3 Hz - 60.5 Hz			
Rated grid voltage / rated power frequency	240 V / 60 Hz			
Max. continuous output current	12.5 A	15.8 A	21 A	25 A
Max. Output Overcurrent Protection	20 A	23.8 A	30 A	35 A
Trip Limit Accuracy	≤±2%			
Trip Time Accuracy	≤16.67ms			
Power factor at rated power	≥0.99			
Feed-in phases / connection phases	2 / 2			
<b>Efficiency</b>				
Max. efficiency / CEC weighted efficiency	97.7% / 97%			
<b>Protective devices</b>				
DC disconnect device / AC disconnect device	● / -			
Ground fault monitoring / grid monitoring	● / ●			
DC reverse polarity protection / AC short-circuit current capability	● / ●			
Galvanic isolation	-			
All-pole-sensitive residual-current monitoring unit	●			
Arc-fault circuit interrupter (according to UL 1699B)	●			
Protection class (according to IEC 62103) / overvoltage category (according to IEC 60664-1)	I / II (DC), III (AC)			
<b>General data</b>				
Dimensions (W / H / D)	15x23.8x8 in (380x580x203 mm)			
Weight	57.3lb (26kg)	60.6lb (27.5kg)	64lb (29kg)	66lb (30kg)
Operating temperature range	-25~+60°C (-13~140°F)with derating above45°C(113°F)			
Noise emission	<40	<45	<45	<50
Self-consumption (night)	<3 W			
Topology	Transformerless			
Cooling concept	Convection	Convection	Convection	Fan speed control
Degree of protection (according to IEC 60529)	NEMA 3R (IP65)			
Max. permissible value for relative humidity (non-condensing)	95%			
<b>Features</b>				
DC connection / AC connection	Srew terminal / Srew terminal			
Display	2-line LCD			
Interface: Wi-Fi / Ethernet	● / ●			
Warranty: 5 / 10 / 15 / 20 years	● / ○ / ○ / ○			
Certificates and approvals (additional on request)	UL1741, IEEE1547, FCC Part 15 (Class A & B), CSA C22.2 No. 107.1-2001, UL1699B			



● Standard features ○ Optional features - Not available

	SolarRiver 7000TLA-US	SolarRiver 7600TLA-US	SolarRiver 9000TLA-US	SolarRiver 10000TLA-US
<b>Input (DC)</b>				
Max. DC power	7700 W	8360 W	9900 W	11000 W
Maximum Usable Power for Each Channel	5400 W	5400 W	6400 W	6400 W
Max. input voltage	550 V			
Full load MPP voltage range / rated input voltage	200 V - 500 V / 400V		230 V - 500 V / 400 V	
Min. input voltage / initial input voltage	100 V / 150 V			
Max. input current for both MPPT in Parallel	34A	37 A	44 A	48 A
Max. usable current per channel (not including Full load MPP voltage range)	24 A			
Max. Input Short Circuit Current per channel	25 A			
Max. Utility Backfeed Current to PV array	0 A			
Number of independent MPP inputs	2			
Number of strings	5			
<b>Output (AC)</b>				
Rated power (@ 240 V / 60 Hz)	7000 W	7600 W	9000 W	10000 W
Max. apparent AC power	7700 VA	8360 VA	9900 VA	11000 VA
Nominal AC voltage / range	240 V / 211 - 264 V			
AC power frequency / range	60 Hz / 59.3 Hz - 60.5 Hz			
Rated grid voltage / rated power frequency	240 V / 60 Hz			
Max. continuous output current	29.2 A	32 A	37.5 A	42 A
Max. Output Overcurrent Protection	45 A	50 A	55 A	65 A
Trip Limit Accuracy	≤±2%			
Trip Time Accuracy	≤16.67ms			
Power factor at rated power	≥0.99			
Feed-in phases / connection phases	2 / 2			
<b>Efficiency</b>				
Max. efficiency / CEC weighted efficiency	98% / 97.5%			
<b>Protective devices</b>				
DC disconnect device / AC disconnect device	● / -			
Ground fault monitoring / grid monitoring	● / ●			
DC reverse polarity protection / AC short-circuit current capability	● / ●			
Galvanic isolation	-			
All-pole-sensitive residual-current monitoring unit	●			
Arc-fault circuit interrupter (according to UL 1699B)	●			
Protection class (according to IEC 62103) / overvoltage category (according to IEC 60664-1)	I / II (DC), III (AC)			
<b>General data</b>				
Dimensions (W / H / D)	18.5x27.6x9.1 in (470x700x203 mm)			
Weight	93.7lb (42.5kg)		95.9lb (43.5kg)	
Operating temperature range	-25~+60°C (-13~140°F)with derating above45°C(113°F)			
Noise emission	<50		<55	
Self-consumption (night)	<3 W			
Topology	Transformerless			
Cooling concept	Fan speed control			
Degree of protection (according to IEC 60529)	NEMA 3R (IP65)			
Max. permissible value for relative humidity (non-condensing)	95%			
<b>Features</b>				
DC connection / AC connection	Srew terminal / Srew terminal			
Display	2-line LCD			
Interface: Wi-Fi / Ethernet	● / ●			
Warranty: 5 / 10 / 15 / 20 years	● / ○ / ○ / ○			
Certificates and approvals (additional on request)	UL1741, IEEE1547, FCC Part 15 (Class A & B), CSA C22.2 No. 107.1-2001, UL1699B			



**SAMIL POWER**  
Expert for PV Grid-tied Inverters

**Samil Power Co., Ltd. (China)**

Sales and Service Center, Wuxi  
No.52, Huigu Innovation Park, Huishan District, Wuxi,  
Jiangsu Province, 214174 P.R.C  
T: +86 (0) 510 8359 3132  
F: +86 (0) 510 8181 9678  
E: [info@samilpower.com](mailto:info@samilpower.com)

**Samil Power Ausco Pty Ltd. (Australia)**

Sydney Business and Technology Centre  
Unit 5/2 Railway Parade  
Lidcombe NSW 2141  
T: +61 (0) 2 9643 7788  
E: [australia@samilpower.com](mailto:australia@samilpower.com)

**Samil Power Co., Ltd. (China)**

Factory, Suqian  
No.6 Xuefengshan Road,  
Suyu District, Suqian,  
Jiangsu Province, 214174 P.R.C

**Samil Power US Ltd. (USA)**

3478 Buskirk Avenue, Suite 1000,  
Pleasant Hill, CA 94523  
T: +1 (925) 930 3924  
E: [usa@samilpower.com](mailto:usa@samilpower.com)

**Samil Power UK Ltd. (UK)**

Unit 49 Suttons Business Park Suttons Park Avenue  
Reading RG6 1AZ  
T: +44 (0) 11898 44481  
F: +44 (0) 11898 44745  
VAT Number: 129 3120 38

**Samil Power s.r.l. (Italia)**

Sede legale: C.so P.ta Vittoria 18  
20122 Milano  
T: +39 02 45 077 584  
F: +39 02 40 043 490  
E: [italy@samilpower.com](mailto:italy@samilpower.com)

**Samil Power France SARL (France)**

E: [france@samilpower.com](mailto:france@samilpower.com)

**Support Center Australia**

E: [service-australia@samilpower.com](mailto:service-australia@samilpower.com)

**Support Center Nederland**

E: [service-netherlands@samilpower.com](mailto:service-netherlands@samilpower.com)

**Support Center Deutschland**

E: [service-germany@samilpower.com](mailto:service-germany@samilpower.com)

**Support Center UK**

E: [service-uk@samilpower.com](mailto:service-uk@samilpower.com)

**Centro Assistenza Italia**

E: [service-italy@samilpower.com](mailto:service-italy@samilpower.com)

**Support Center USA**

E: [service-usa@samilpower.com](mailto:service-usa@samilpower.com)

