

# Rolls



## FLOODED DEEP CYCLE BATTERY

2 YS 27P



Series	5000	Warranty	5 Years
Volts	2	BCI	SPEC
Cells	1	Plates/Cell	27
Terminal Type	Flag		
Included Hardware	S/S Hex Cap Screw, Nut, Lock & Flat Washer		
Size & Thread	5/16"-18		
Cables	19" 4/0 interconnect cables *RE incl.		

### Charge

Charge Voltage Range	2.45-2.5 V/cell @ 25°C (77°F)
Float Voltage Range	2.25 V/cell @ 25°C (77°F)
Self-Discharge Rate	5%-10% per month at 25°C (77°F)

### Capacity

Cold Crank Amps (CCA) 0°F / -17°C	4975
Marine Crank Amps (MCA) 32°F / 0°C	6219
Reserve Capacity (RC @ 25A)	5257 Minutes
Reserve Capacity (RC @ 75A)	1752 Minutes

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 100 Hour Rate	<b>2825 AH</b>	<b>28.25 A</b>
@ 72 Hour Rate	<b>2672 AH</b>	<b>37.11 A</b>
@ 50 Hour Rate	<b>2530 AH</b>	<b>50.59 A</b>
@ 20 Hour Rate	<b>2190 AH</b>	<b>109.51 A</b>
@ 15 Hour Rate	<b>2037 AH</b>	<b>135.79 A</b>
@ 10 Hour Rate	<b>1949 AH</b>	<b>194.93 A</b>
@ 8 Hour Rate	<b>1884 AH</b>	<b>235.45 A</b>
@ 5 Hour Rate	<b>1752 AH</b>	<b>350.44 A</b>
@ 1 Hour Rate	<b>986 AH</b>	<b>985.61 A</b>

Amphere hour capacity ratings based on specific gravity of 1.280 at 25°C (77°F). Reduce capacities 5% for specific gravity of 1.265 and 10% for 1.250.

### Specifications




SAI GLOBAL  
ISO 9001  
Quality

Weight	111.5 kg	246 lbs
Length	35.6 cm	14"
Width	22.9 cm	9"
Height Inc. Term.	80.3 cm	31.63"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process, battery components & electrolyte levels.

Electrolyte Reserve	95 mm	3.75"
Container (Inner)	Polypropylene	
Cover (Inner)	Polypropylene - heat sealed to inner container	
Container (Outer)	High Density Polyethylene	
Cover (Outer)	High Density Polyethylene snap fit to outer container	
Handles	Molded	

### Cycle Life vs. Depth of Discharge



### Voltage vs. Depth of Discharge

