



RENEWABLE ENERGY LINE

FLOODED DEEP CYCLE BATTERIES

CLICK FOR IMPERIAL DIMENSIONS



SERIES	MODEL	20 HR RATE	100 HR RATE	BCI	TERMINAL TYPE	PLATES PER CELL	LENGTH (cm)	WIDTH (cm)	HEIGHT (cm)	WEIGHT (DRY) (kg)	WEIGHT (WET) (kg)
2 VOLT											
4000	S-1440	1124	1452	L-16	2V L-16	43	31.75 cm	18.10 cm	43.18 cm	38.56 kg	54.43 kg
4000	S-1660	1284	1660	L-16	2V L-16	49	31.75 cm	18.10 cm	43.18 cm	40.37 kg	57.61 kg
4000	S-1860	1445	1869	L-16	2V L-16	55	31.75 cm	18.10 cm	43.18 cm	43.54 kg	59.42 kg
4500	S-1400EX	1000	1408	L-16	2V L-16	29	31.75 cm	18.10 cm	42.55 cm	42.27 kg	57.15 kg
5000	2 KS 33P	1766	2490	SPEC.	FLAG RR	33	39.21 cm	21.11 cm	63.02 cm	65.91 kg	94.35 kg
5000	2 OS 33P	1880	2655	SPEC.	FLAG RR	33	39.21 cm	21.11 cm	63.02 cm	70.45 kg	100.70 kg
5000	2 YS 27P	2106	2969	SPEC.	FLAG RR	27	39.37 cm	22.86 cm	80.33 cm	77.11 kg	111.58 kg
5000	2 YS 31P	2430	3426	SPEC.	FLAG RR	31	39.37 cm	22.86 cm	80.33 cm	90.91 kg	129.27 kg
5000	2 YS 62P	4860	6853	SPEC.	FLAG RR	31	69.53 cm	22.86 cm	80.33 cm	181.44 kg	258.55 kg

4 VOLT											
5000	4 CS 17P	546	770	SPEC.	FLAG RR	17	36.51 cm	20.96 cm	46.36 cm	44.55 kg	58.06 kg
5000	4 KS 21P	1104	1557	SPEC.	FLAG RR	21	40.01 cm	23.81 cm	62.87 cm	98.18 kg	121.11 kg
5000	4 KS 25P	1350	1904	SPEC.	FLAG RR	25	40.01 cm	26.99 cm	62.87 cm	100.00 kg	142.88 kg
5000	4 KS 27P	1460	2062	SPEC.	FLAG RR	27	40.01 cm	26.99 cm	62.87 cm	113.18 kg	153.77 kg

6 VOLT											
4000	S-290	220	290	GC2	UNIV Molded	19	25.88 cm	18.10 cm	27.94 cm	26.82 kg	30.84 kg
4000	S-330	250	330	GC2H	UNIV Molded	17	25.88 cm	18.10 cm	28.96 cm	26.82 kg	35.83 kg
4000	S-480	375	486	L-16	FLAG M	15	31.75 cm	18.10 cm	42.55 cm	36.74 kg	51.26 kg
4000	S-550	428	532	L-16	FLAG M	17	31.75 cm	18.10 cm	42.55 cm	42.64 kg	55.79 kg
4000	S-605	468	605	L-16	FLAG M	18	31.75 cm	18.10 cm	42.55 cm	44.90 kg	56.70 kg
4000	6 HHG 31P	344	458	SPEC.	FLAG RR	31	52.71 cm	20.32 cm	30.16 cm	43.64 kg	56.70 kg
4000	6 EHG 31P	410	545	SPEC.	FLAG RR	31	52.71 cm	20.32 cm	32.39 cm	47.27 kg	60.33 kg
4000	FC-420	315	419	L-16	FLAG M	15	31.75 cm	18.10 cm	42.55 cm	35.38 kg	51.71 kg
4500	S-500EX	357	504	L-16	FLAG M	11	31.75 cm	18.10 cm	42.55 cm	42.73 kg	58.97 kg
5000	6 CS 17P	546	770	SPEC.	FLAG RR	17	55.88 cm	20.96 cm	46.36 cm	80.91 kg	100.24 kg
5000	6 CS 21P	683	963	SPEC.	FLAG RR	21	55.88 cm	24.77 cm	46.36 cm	98.64 kg	122.92 kg
5000	6 CS 25P	820	1156	SPEC.	FLAG RR	25	55.88 cm	28.58 cm	46.36 cm	115.45 kg	144.24 kg
5000	6 CS 27P	893	1253	SPEC.	FLAG RR	27	55.88 cm	28.58 cm	46.36 cm	124.09 kg	155.13 kg

4000 SERIES - 2 year full replacement + 5 year pro-rated warranty

4500 SERIES - 3 year full replacement + 4 year pro-rated warranty

5000 SERIES - 3 year full replacement + 7 year pro-rated warranty



RENEWABLE ENERGY LINE

FLOODED DEEP CYCLE BATTERIES



SERIES	MODEL	20 HR RATE	100 HR RATE	BCI	TERMINAL TYPE	PLATES PER CELL	LENGTH (cm)	WIDTH (cm)	HEIGHT (cm)	WEIGHT (DRY) (kg)	WEIGHT (WET) (kg)
8 VOLT											
4000	8 HHG 31P	344	458	SPEC.	FLAG RR	31	68.58 cm	20.32 cm	30.16 cm	58.18 kg	75.75 kg
4000	8 EHG 31P	410	545	SPEC.	FLAG RR	31	68.58 cm	20.32 cm	32.39 cm	62.73 kg	80.74 kg
5000	8 CS 17P	546	770	SPEC.	FLAG RR	17	71.76 cm	20.96 cm	46.36 cm	108.18 kg	133.36 kg
5000	8 CS 25P	820	1156	SPEC.	FLAG RR	25	71.76 cm	28.58 cm	46.36 cm	155.45 kg	192.32 kg

12 VOLT											
4000	S-105	85	115	24	UNIV Molded	7	27.94 cm	17.15 cm	23.80 cm	15.88 kg	20.87 kg
4000	S-140	105	140	27	UNIV Molded	9	32.10 cm	17.15 cm	23.80 cm	18.60 kg	24.49 kg
4000	S-160	120	160	30H	UNIV Molded	11	34.29 cm	17.15 cm	24.13 cm	27.27 kg	33.11 kg
4000	S-180	136	181	Compact 125	UNIV	11	34.29 cm	17.15 cm	29.53 cm	32.73 kg	40.82 kg
4000	S-260	200	266	250	UNIV	9	39.05 cm	17.78 cm	36.51 cm	44.09 kg	56.70 kg
5000	12 CS 11P	357	503	SPEC.	FLAG L	11	55.88 cm	28.58 cm	46.36 cm	100.00 kg	123.38 kg

4000 SERIES - 2 year full replacement + 5 year pro-rated warranty

4500 SERIES - 3 year full replacement + 4 year pro-rated warranty

5000 SERIES - 3 year full replacement + 7 year pro-rated warranty